

CONGRATULATIONS - you've made a smart move purchasing this powerful sales tool. It's very important to assemble your display with attention to detail – just like your tint jobs! Imagine what prospects might think if they see dirt in the film, bad film cuts or crooked labels. Once assembled perfectly, place your new display in front of curious prospects in your office, a car dealership waiting room or next to the cashier at a local car wash.

Components

With these items, dealers can build a custom display for any of the Express auto films available.

- 1) Tempered glass panel
- 2) Aluminum base with rubber sleeve
- 3) Product series labels
 - Ceramic
 - High Performance
 - Non Reflective
- 4) Warranty coverage labels
 - Lifetime color stable
 - 7 year color stable
 - 7 year
- 5) Performance specification labels
 - All automotive films



Assembled display with aluminum base and all labels centered and balanced perfectly.



Assembly

- 1) Install film samples you sell from an Express product line - adjust widths accordingly.
- 2) Remove rubber sleeve from aluminum base - place glass (with cured film) completely into the bottom of the rubber sleeve – make sure you center the glass left-to-right.
- 3) Place glass panel (with rubber sleeve) into the top of the aluminum base. The fit will be very snug.
NOTE: Filmed side of glass should be on the back of the display.
- 4) Install the appropriate product series label on the front (curved) portion of the aluminum base - centered left-to-right and top-to-bottom.
- 5) Install the appropriate warranty coverage label over the product series label, towards the right side as shown on the assembled display image.
- 6) To identify the film samples, install applicable performance specification labels on glass directly above aluminum base - centered on each film.